

CORRECTED
VERSION *

PCT


WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 5 : G08G 3/02, 5/04	A1	(11) International Publication Number: WO 93/01576 (43) International Publication Date: 21 January 1993 (21.01.93)
(21) International Application Number: PCT/SE92/00485 (22) International Filing Date: 29 June 1992 (29.06.92) (30) Priority data: 9102034-7 1 July 1991 (01.07.91) SE 9102362-2 15 August 1991 (15.08.91) SE 9103542-8 28 November 1991 (28.11.91) SE (71)(72) Applicant and Inventor: LANS, Håkan [SE/SE]; Ringvägen 56E, S-133 35 Saltsjöbaden (SE). (74) Agent: BERG, S., A.; H. Albihns Patentbyrå AB, Box 3137, S-103 62 Stockholm (SE).		(81) Designated States: AU, BB, BG, BR, CA, CS, FI, HU, JP, KP, KR, LK, MG, MW, NO, PL, RO, RU, SD, US, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IT, LU, MC, NL, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, SN, TD, TG). Published <i>With international search report.</i>

(54) Title: A POSITION INDICATING SYSTEM



(57) Abstract

A plurality of movable objects as aircraft are provided with GPS receivers, enabling the individual determination of longitude and latitude. Further, the receiver will also give a very precise time. According to the invention, this precise time is used to enable all objects of the plurality to transmit in a predetermined radio frequency their identities and positions in precisely determined time blocks. By allocating the frequencies in VHF or UHF, the range of receivability is limited, such that the system may be worldwide. Transmissions may be received by all the participants as well as by air traffic monitoring centers at ground.

* (Referred to in PCT Gazette No. 03/1994, Section II)

BEST AVAILABLE COPY

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	FR	France	MR	Mauritania
AU	Australia	GA	Gabon	MW	Malawi
BB	Barbados	GB	United Kingdom	NE	Niger
BE	Belgium	GN	Guinea	NL	Netherlands
BF	Burkina Faso	GR	Greece	NO	Norway
BG	Bulgaria	HU	Hungary	NZ	New Zealand
BJ	Benin	IE	Ireland	PL	Poland
BR	Brazil	IT	Italy	PT	Portugal
BY	Belarus	JP	Japan	RO	Romania
CA	Canada	KP	Democratic People's Republic of Korea	RU	Russian Federation
CF	Central African Republic	KR	Republic of Korea	SD	Sudan
CG	Congo	KZ	Kazakhstan	SE	Sweden
CH	Switzerland	LJ	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovak Republic
CM	Cameroon	LU	Luxembourg	SN	Senegal
CN	China	LV	Latvia	TD	Chad
CS	Czechoslovakia	MC	Monaco	TG	Togo
CZ	Czech Republic	MG	Madagascar	UA	Ukraine
DE	Germany	ML	Mali	US	United States of America
DK	Denmark	MN	Mongolia	UZ	Uzbekistan
ES	Spain			VN	Viet Nam
FI	Finland				

A position indicating system

5 BACKGROUND OF THE INVENTION

The invention regards a system for indicating the positions of movable objects, which enables for a population of movable objects or stations to keep trace of one another and for a
10 central station or a number of central stations, in some cases, to keep trace of the positions of individual and/or all the members of that population.

Systems for the determination of position are well-known
15 since a very long time, e.g. the DECCA system, the LORAN system, the VLF OMEGA system, NDB, VOR and DME. For the use of central stations, there are known different types of radar systems, such as primary radar (PSR) and secondary surveillance radar (SSR). The SSR radar system includes a ground
20 based interrogator and SSR Transponders in the movable objects.

In recent times has been created the American GPS (Global Positioning SYSTEM) and a Russian corresponding system called
25 GLONASS, which both build on time signals sent from satellites having known orbit elements. When at least four such satellites are above the horizon, it is possible to obtain locally an unequivocal position with a very high accuracy. Devices for obtaining such position information are well-
30 known and commercially available, making it superfluous here to describe them in more detail than is necessary for the description of the present invention.

The fact that a precise position can be obtained with equipment having a reasonable price has led to its proposed use
35 for navigating and surveillance for e.g. aviation, the congestion of which has become notorious in recent years. According to GB-A-2 155 720, it has been proposed to include in an aircraft Transponder response to an interrogation from a

control station, not only its usual identification response, but also the position determined by GPS of the movable object carrying the transponder.

5 In US patent 4,835,537, hereby included by reference, it is proposed to obtain an anti-collision system where aircraft, runways, fixed obstacles and land vehicles on airports signal their positions to all participants. Thereby, the signaling is made in a single radio channel for all participants, each participant seeking a moment when the channel is unoccupied
10 and starting signalling its message after the lapse of a random wait time. The transmitting power is held at a low level in order not to exceed an air volume radius of a monitored airspace.

15 At present, the responsibility to monitor and control the air traffic around the earth is divided into a number of Area Control Centers (ACC) or Flight Information Centers (FIC), each of them having responsibility over dedicated regions (Flight Information Regions - FIRs) within which ground
20 monitoring and control of air traffic operationg in certain or all parts of the airspace and/or to provid certain services to aircraft which have filed a flight plan. Each time a aircraft leaves one of those FIRs, the control center of the next FIR is notified about the trajectory taken, so that the
25 aircraft can be detected or identified. Before entering into the next FIR the crew of the aircraft is ordered to establish radio contact with the control center which FIR the aircraft is about to enter.

30 The air traffic must follow a limited number of air corridors, often called "airways", or predetermined routes. The airways are established along ground based radio navigation beacons or by a combination of the locations of such radio
35 navigation beacons and "fixed points" determined by the distance and bearing to/from such ground based beacons. The aircraft are navigating by means of receivers on board which can detect the signals from the ground based radio navigation beacons and has a display unit which shows the ocation of the

5 aircraft in relation to the ground based beacon. Over and in
the vicinity of land also the control centers are monitoring
and controlling the movements of aircraft by radar. The
minimum lateral separation between aircraft flying at the
10 same altitude in these radar controlled areas can vary between normally 5 - 10 nautical miles. On final approach to an airport, the minimum radar separation between aircraft is typically 3 nautical miles. In areas without radar coverage, the minimum separation for air traffic at the same altitude and track is normally 10 minutes, which, depending on the speed of the aircraft, corresponds to a distance of up to 80 - 90 nautical miles.

15 Air traffic over the oceans follows predetermined routes. Due to the fact that it is not possible to determine an aircraft position by means of ground based radio beacons or by radar when operating over the oceans, the separation between aircraft must be significantly increased. Normally, the minimum lateral separation between aircraft flying on the same track and at the same altitude is, as in the case over the North Atlantic, 60 nautical miles.

20 At present, the number of airways and routes is limited, and aircraft have to be confined to so-called "slots", which are apportioned to the air companies or to the individual aircraft, often very long in advance. Should an aircraft by any reason be delayed for a few minutes on the ground, and miss its slot, this may cause additional delays of up to several hours before the aircraft can obtain a new free slot.

30 Special flow management or flow control units are established in many areas of the world. The need for these flow management units and the slot allocation procedures is caused by the lack of capacity in the airways system, along the flight routes and at the busy airports.

35 At airports, the capacity is limited by a number of different factors. Basically, the number of runways, taxiways and aircraft gates, meteorological conditions, navigation and landing equipment, air traffic control procedures, etc., are

important elements which separately or collectively affect the capacity. In situations with poor visibility, the capacity problems are increasing, mainly due to the inability of present technology to provide air traffic control with the capability to monitor and control aircraft and ground vehicle movements. The runway occupancy times are also increasing as aircraft have to taxi at lower speeds due to difficulties to navigate on the ground in poor visibility. This also reduces the airport capacity.

The number of incidents and fatal accidents caused by potential or actual collisions between aircraft on the ground and aircraft and ground vehicles has increased over the last decades. The number of such serious incidents reported in the USA is in the order of 5 - 7 per 100,000 take-off and landings. A number of fatal accidents have occurred over the years.

A system which can offer the possibilities for air traffic control to monitor and control aircraft ground operations as well as ground vehicle movements, having each member in the system transmitting its position and identification, presenting that information presented to air traffic control, e.g. on a display, as well as providing the same information to the pilots, and which information could also be used to guide the aircraft movements would be of significant importance to the improvement of airport capacity and safety.

The capacity and safety problems are expected to become worse as air traffic is forecasted to continue to grow at a relatively high rate. A doubling of the present number of air passengers (approx. 1.2 billion) and an almost proportional increase thereto of the number of aircraft operations is expected over the next 10 - 12 years.

According to a spokesman for the German Aerospace Research Establishment, "If we could get one additional landing per hour at Frankfurt, over a year it would mean 10 million

deutschmarks savings in delays." (New scientist 16 November 1991 p. 23).

5 Several international working groups have been established to review the present situation and to recommend actions to be taken to improve the capacity of the present air navigation an air traffic control system, as well as for the improvement of the safety on the ground. Several of these working groups are conducting their work under the auspices of the Interna-
10 tional Civil Aviation Orgainzation - ICAO. In several countries, especially in the USA, significant efforts are being made to solve the safety problems related to ground operations at airports.

15 Thus, it is globally recognized that there is a shortage of capacity and that significant economic savings are possible if systems which can provied an improved capability to control and monitor the air traffic can improve both safety and capacity.

20

OBJECTS AND SUMMARY OF THE INVENTION

25 It is a general object of the invention to obtain a system for the control of a population of movable entities as to their locations, by each member sending out own positions in a common radio channel, and which admits even very large populations, for avoiding collisions and admitting of central control. Populations envisaged can be aircraft, ground ve-
30 hicles or ships. In order for such a system to work optimally, it is necessary to avoid not only collisions of a purely physical nature, but also collisions of a communica- tions nature, both as concerns actual collisions meaning that more than one participant transmits simultaneously so that
35 they disturb each other, and inability to transmit due to congestion of the common communication channel.

Specifically for aviation purposes, it is an object to obtain a system which can be used by an aircraft everywhere without

exception. Collision risks are naturally highest where traffic is dense, but random accumulations of aircraft could pop up practically anywhere around the earth.

5 A further object for aviation puposes is to create a better possibility of distributing aircraft, in order to increase the airspace capacity, by avoiding the necessity of the beacon infrastructure through a distributed localization, each aircraft having its own means enabling it to follow any
10 predetermined corridor or route, which does not have to be materialized by common landbased hardware. Particularly where beacon systems have not yet been installed, great savings are possible in this respect. Further, when routes may be defined which do not depend on a beacon system, the number of routes
15 may be increased practically at will, and it is possible to avoid present congestion at least outside the neighbourhood of airports. Bottlenecks in takeoff and landing can also be avoided to a great extent if systems for air traffic control are improved, so that lateral and/or vertical separation
20 between aircraft can be reduced and the airspace capacity can be improved without increased collision risk.

On long-haul flights over sea or uninhabited areas, there is presently no systems available for accurate surface control
25 of aviation, since the aircraft cannot be detected by e.g. radar. It is a further object of the invention to enable aircraft in such positions to be able to report their positions to central control, preferentially by satellite communication, and the frequency of the reporting may then be
30 decided in the aircraft in dependence of local traffic intensity, to be determined by the system.

Said objects and other objects and advantages are obtained, according to the invention, by means of a position indicating
35 system comprising a population of simultaneously active movable stations, which each sense their geographical positions through the reception of signals from geometrically distributed transmitters having known positions, and wherein each participating station has a transmitter for sending out

in a radio channel common to the system of signals indicating own identities and geographical positions, and memory means for storing of signals from other participating movable stations, and whereby according to the invention each station has handling means, as a computer, comprising a time base which is precision controlled by time signals received from said geometrically distributed transmitters, said time base defining time blocks standardized thereto and enumerable in a predetermined, repetitive maximum frame, said memory means registering free time blocks where no transmission is perceived, means for selecting one of said free time blocks for own repetitive transmission of identity and position therein, said transmitter working in a frequency having a range substantially confined to the line of sight, and preferably means for randomly switching of a used one of said time blocks for another block registered as free. According to a preferred embodiment, each station also determines traffic density in its environment and decides in function thereof how many time blocks are to be used in successive frames.

It is preferred to have in each station a monitor or the like, to show the locations of other stations superimposed on e.g. a map. Another advantageous feature is the determination of actual risk of collision due to geographical neighbourhood, for warning the crew with a danger signal. As there is an established network of ground control centers (Area Control Centers - ACC or Flight Information Centers - FIC) for the control or monitoring of all air traffic movements, all aircraft movements should be reported to ground, so that in principle only air traffic control can allocate a change of routing including altitude. In uninhabited regions, the signalling of dangerous congestion to the ground control centers should be made by satellite communication.

A particular safety and redundancy feature is the possibility to use the transmission from other movable objects and/or ground stations for secondary localization purposes. If an aircraft loses the facility of satellite localization, it is possible for that aircraft to keep its timebase working by

5 synchronizing to the other movable objects' and/or ground stations' transmissions, and since those aircraft are emitting position signals, in precise timing according to good timing in UTC time, they may serve as a secondary system of geometrically distributed transmitters, replacing the satellites.

10 According to a preferred embodiment of the inventive system, it is intended that a ground station, e.g. at an airport, shall be able to order nearby aircraft to stop transmitting spontaneously and switch over to transmitting in ordered mode in time blocks in the maximum frame, which are designated by the station. The ground station would need to give this order only once, which means a great saving in canal occupation
15 compared to conventional polling. In comparison to presently used radar surveillance, there is the certain advantage that aircraft coming in towards an airport will not be shading each other even if they come in at a common direction. The order from the ground station may be modified for more frequent transmission when the aircraft come closer i.e. for
20 sending several times in each maximal frame.

25 According to another preferred embodiment, the same system may be used for tracking ground traffic on e.g. an airport. Each vehicle allowed on the airfield would then carry a complete system, which signals to the ground control unit concerned and may also be received by the other vehicles or aircraft. At least the ground control station would then have a display with a map showing the movements of all the vehicles and aircraft, and also the vehicles may be similarly
30 provided if desired. Aircraft similarly equipped will be shown as well. In view of the fact that large airports may have hundreds of vehicles and aircraft moving around, the system would greatly contribute to improving the safety.

35 The local time bases can be made extremely precise when working in the GPS system, since each of the satellites emits time signals in UTC time. In order to calculate the position, a minimum of four satellites must be received, there being

unknown three space coordinates and time. Since the speed of light is known, the respective distances to the satellites and the true UTC time are determined from those time signals. (If the altitude is known, theoretically only three satellites are necessary). It can then be counted on to have an accuracy in UTC time available to about 100 ns. Evident military considerations have led to a time jitter of random character being added to the satellite time signals (called Selective Availability - S/A), making it necessary for very exact position determination to have access to a ground station (called Reference Station) within coverage for compensating this time jitter. However, the time accuracy is quite sufficient for the purposes of the invention, as each station has access to a timebase having this kind of accuracy.

Instead of using such a high-precision time normal, it is also possible to arrange for one of the movable stations to be designated as a time master by drawing lots. In view of the good standard time available from the GPS satellites, it is preferred to utilize this time. However, if the GPS satellite receiver of one station fails, the timers of the other movable stations may be used as a reserve facility. If the GPS satellites themselves fail, resort may be taken to the signals sent in the transmission channel by existing fixed stations in airports, and the movable stations would be able to transmit their positions as known, giving a positioning system which is inferior but still usable in the emergency.. According to the invention, therefore, each movable station utilizes for transmission time blocks defined by a common timebase. Each station attempts to select time blocks which are not occupied by another station. Simultaneously, each station listens to the predetermined radio frequency and determines the relative positions of at least the nearest neighbors in relation to the own position. The own station determines going out therefrom how often it shall transmit. An aircraft over empty sea may perhaps send out its position once a minute, whereas another aircraft in very heavy traffic would have to send out its position in very short intervals.

In accordance with a preferred embodiment, the risk of colliding transmissions can be greatly diminished, in that an autonomously transmitting station may signal an indication in a regular transmission that it is going to switch time block and to which time block of those which are free the switching is to be made. This information is sent in the last message in the old block and possibly in one or more preceding sendings in this block. The other participants will then know this and will not collidingly appropriate this time block. A newcomer will listen to one or more maximal frames before transmitting and will therefore not try to transmit in a time block which is thus pre-appropriated. Thus, this type of collision could hardly occur except in the rare case when two newcomers are simultaneously entering and by chance both occupy a free time block. The probability of this is further diminished by the fact that entering the system is normally done when starting from an airport and will start transmitting ordered by the central control there.

The invention is not limited to use in air traffic or at sea, but can also be used on land, in order to keep trace of trains, trucks, taxis or even animals provided with the necessary equipment. In certain cases and according to a particular embodiment, the central may order a participant to send more than its own position. Each station has stocked in its memory the positions of other movable stations, the signals of which it has received. It is then possible for the central station to demand the transmission of this memory content, making it possible for stations to be located, the transmissions of which have perhaps not been received by the central station.

Going out from the fundamental idea that all the movable stations in the system have an accurate time base, the allocation of time blocks can be made in many ways, their length may be selected in many ways, as also the signaling speed and thereby the utilized bandwidth.

In a representative case, and depending on the circumstances, the exchanged information in each transmission may be 150-200 bits. With a transmission speed of 9600 baud, such a message takes a maximum of slightly over 20 ms. To switch from reception mode to transmission mode takes time, 1-3 ms, and since a station must listen to all time blocks where it is not transmitting itself, it is necessary to arrange such dead time first in each time block, compensating for speed of light and making it possible for a transmitting station to listen to an eventual message in the next following time block. A suitable length of the time block could then be 26.66 ms, so that each minute comprises 2250 time blocks. For practical reasons, it is suitable to let a certain period, e.g. one minute, be a kind of maximal frame.

Each station listens to the traffic in the allocated frequency and registers in its memory which time blocks are free, and also the position etc. for those stations, the signals of which are detected. This information is automatically treated in order to determine how near the neighbors are and how often the own transmission shall be made. Those who have no near neighbors do not need to transmit often, e.g. only twice or a few times per minute.

The information may also be treated for showing on a monitor, In a suitable scale, then, the surrounding stations may be shown, with a vector, the length of which shows speed, and with numbers showing altitude. In contradiction to ordinary radar, this image or map is referred to a fixed coordinate system (plotted). This simplifies greatly the ocular analysis of eventual risks of collision. - In some cases, for instance when the object is to keep order on serving vehicles on an airport for avoiding collisions, it is possible to leave out the monitor in each vehicle, as it is then sufficient if the central control can survey the system on a monitor.

As mentioned, it is envisaged that a station may be active in an autonomous mode or in a ground station ordered mode. In -

autonomous transmission mode, the individual station selects a time block which is not found occupied in previous listening. In order to avoid that more than one station appropriates the same time block and blocks it, something none of them
5 can perceive, being unable of simultaneous transmission and reception, they systematically change the selection of time block, at frequent intervals, using a random number generator (pseudo-random algorithm). For instance, the station may jump for a randomly determined number of occupied time blocks to a
10 free time block. If, as previously explained, the jumping is previously announced and the new time block thus preempted, mutual interference can be practically excluded.

The ordered mode is normally set by an order from a fixed
15 station, e.g. from the air control of an airfield (ground station ordered mode). The fixed station has the same time base and can call movable stations in a free time block, allocating individual time block series to them and making them stop autonomous transmitting, transmitting then only in
20 said time block series. The air control station can then obtain positional information from the selected stations in arbitrary intervals. It is suitable to limit the available time blocks for the ordered mode to, say, 75 % of the whole maximum frame, but even with this limitation, there are
25 available in the above-indicated example some 1685 time blocks per minute. Even if as many as 50 aircraft are to be kept accurate track of, they can then transmit with intervals of about 2 seconds. This should be compared to standard rotating radar systems, the antennas of which rotate slower
30 than some 6-8 seconds per revolution. This example is very schematic, as aircraft are normally transmitting with different rates, and the highest rate is necessary only for aircraft very near to an airport.

35 Also the air traffic control can monitor the traffic on a display in an appropriate scale, and keep a surveillance of a far more precise quality than what has been possible hitherto, particularly so in areas where radar systems cannot or have not been arranged. For countries which have not yet

availed themselves of important ground based air traffic control infrastructure for aircraft control, the present invention could furnish a high-quality, cost effective alternative to an infrastructure investment which may presently be
5 beyond their available means. - Over regions presently outside of radar coverage, movable stations may report by satellite communication the identity, position, altitude etc. to inform responsible ground control centers of all positions, and a ground station may then order an aircraft to change its
10 heading or altitude in order to avoid collisions. In order to arrive at a precise time, thus avoiding crowding and queuing or circling in holding patterns before landing at the airport, air traffic control may suggest that an aircraft should cruise at a certain speed.

15

The invention makes possible several advantages for the air traffic. A first advantage is that it is possible to dispense with aviation corridors - the airways, defined by radio
20 beacons, which have previously led to congestion and sometimes made the flight length between airfields longer than necessary. A second advantage is the improved possibility to keep track aircraft and ground vehicle movements. In many cases, the capacity of a runway can be increased. At dead calm, the air perturbations created by aircraft over the
25 runway may remain during some minutes, but normally, they are very quickly removed by the wind, so that even with weak side wind, the capacity may be increased, as the separation between successive landing or starting aircraft could be diminished without increasing the collision risk. In poor visibility, aircraft could taxi on the ground at higher speed, thus
30 minimizing runway occupancy time and improving the capacity.

In Appendix X there is given an overview of some of the potential applications for civil aviation.

35

In maritime traffic, the great problem is that many seeways and harbors are severely congested, presenting dangers particularly in bad weather, and collisions may have serious consequences not only for the ships themselves. Also here,

the invention may be very valuable. If both the maritime traffic and the air traffic are provided with devices according to the invention, each with its own allocated frequency, a supplementary advantage is possible. With distress at sea, a distressed ship may be permitted to break in at the air traffic frequency to send a MAYDAY message, likely to be caught by the station of an aircraft, in view of its high altitude. The airborne station could then break in at the maritime frequency and reach other ships, which cannot be reached by positional signals from the distressed ship.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 shows a schematic block diagram of a station according to the invention.
Fig. 2 shows a communication processor for a station.
Fig. 3 - 7 show respective flow diagrams for an exemplary computer program.

DETAILED DESCRIPTION OF A PREFERRED EMBODIMENT OF THE INVENTION

EXAMPLE

A movable station shown in Fig. 1 comprises a unit 1 which keeps trace of traffic, a presentation computer 2 and a monitor 3 on which a pilot may survey traffic and observe it visually. Unit 1 comprises a satellite receiver 4 for the GPS system, which receives signals from a plurality of satellites, which signals comprise time signals and orbital elements. In principle, the invention is not limited to the use of the GPS satellites, Also the russian GLONASS system or a combination of GPS and GLONASS can be used to determine the position of a movable object. The Such GPS units are commercially available, e.g. the Magnavox MX 4200 from Magnavox Corp., USA. Therefore, nothing more needs to be said than that such a unit may deliver the geographical position in

longitude and latitude with high precision, altitude with somewhat less precision, and UTC time with very high precision. Further, information on speed and course is available. This information is available for the communication processor 5, which in its turn is connected to a transmitter-receiver 6. The satellite receiver 4 works at 1,4 GHz, whereas the transmitter-receiver works at 141 MHz.

The exemplified communication processor is shown more in detail in Fig. 2.

The following information is sent out at each transmitting event.

1. A start flag and a code indicating spontaneous emission mode or ordered transmission mode. (8 bits)
2. The identity code of the station. (48 bits, 8 signs each of 6 bits)
3. The position in longitude and latitude. (24 bits latitude in 1/1000 min; 25 bits longitude in 1/1000 min)
4. Speed, 11 bits, 2 Kt steps.
5. Flight direction, 12 bits, tenths of degrees.
6. Altitude, 12 bits, 16 Ft steps.
7. Time, 6 bits, when the transmitted values were actual (0 - 60 sec.).
8. Status bits, declaring advance notice of change of blocks etc.
9. A control check sum.
10. An end flag.

As apparent from Fig. 2, the communication processor 5 includes a microprocessor 10, a RAM 11, a program memory PROM 12 and a timer circuit 13, all cooperating via a data bus 14 and an address bus 15. For connection with further units, there is a serial communication circuit 16, and for transmission and reception a synchronous communication co-processor 17. The microprocessor may be a HD64180 chip (Hitachi), and the co-processor a Siemens SAB 82525 (version VA3).

Timer circuit 13, which keeps trace of the time multiplex, is fed from the GPS unit 4 (Fig. 1) with signals time synchronized in UTC via a lead 18 (Fig. 2), receiving a time signal per second and further time information from the GPS system. Drivers 19 and 20 complete for obtaining suitable matching of signals.

The RAM memory 11 stores a catalogue of all received signals from other stations, so that identities and positions are stocked and updated. All receivable participants will be heard within the maximal frame, and in order not to fill the memory with inactual participants, such participants are removed if they are not heard again within a prescribed time. Further, information is stored about which time blocks are free. The communication processor also determines the repetition rate of emission, dependent on density of traffic or on order from a central ground station.

The microprocessor 10 works with software comprising a real time operative system, driving in different priorities a number of different programs:

Program 1 reads and decodes data from a host computer, which may be computer 2 in Fig. 1 or, in case of a fixed control station, its own host. A flow diagram for this program is shown in Fig. 3.

Program 2 reads and decodes data coming from the GPS receiver 4, according to flow diagram in Fig. 4.

Program 3 generates messages and manages transmission and other control features for the transceiver 6 (Fig. 1), according to flow diagram shown in Fig. 5.

Program 4 supports the reception and decoding of received data messages from the transceiver, and updates the directory of the other users including mapping of time blocks or time slots as occupied, according to the flow diagram of Fig. 6.

Program 5 keeps the user directory updated by removing participants who have stopped being heard, either because they have landed and shut off or because they are now beyond reach. Further, the own report rate is calculated, e.g. by calculating how many neighbors are within a predetermined

distance. A lowest transmission rate is predetermined and not to be fallen below of. Further, the radio channel load is determined. A flow diagram of program 5 is shown in Fig. 7.

5 Presentation computer 2 fetches its data from the catalogue in the memory of the communication processor and manipulates the information, in part for the needs of the monitor, and in part for enabling the signaling to the pilot for action which may be needed. As during long hauls, the level and frequency
10 of stimuli are low, it is difficult to keep full attentiveness, and it is therefore very valuable to be able to make precise signals demanding attention, according to certain criteria (another station nearby, on its way to the own station, etc.).

15 For proper functioning, it is particularly important for all stations to dispose of a time base having good security. In the Example, this is accomplished in the timer circuit 13, which, receiving once per second a time pulse from the GPS
20 unit, can synchronize the clock frequency of the processor within the demanded accuracy, that is, so that the time blocks assigned or appropriated can be held.

It is also possible, if for some reason the GPS receiver of a
25 station lapses, to take help from the time signals received from neighboring stations, including ground stations. The signals received by radio may be used as another plurality of geometrically distributed transmitters having known positions. The accuracy of the position would of course suffer.
30 It is then preferred to include in the message an information that the position information is less accurate. Should the GPS satellites fail for some reason, an unlikely event, the system may still work to a limited degree as long as the plurality of ground stations can keep a common time, e.g.
35 with accurate clocks which might be calibrated from a chosen satellite out of the geostationary satellites in existence.

It is necessary, in order to make the present system useful as a worldwide system, that a common protocol is used for

frequencies to be used as well as for the disposition of for example time blocks and frames. The present Example can therefore only be seen as a non-limiting example of the application of the invention, as will be readily understood by the man of the art.

POTENTIAL APPLICATIONS OF THE GP&C GNSS CONCEPT

FUNCTIONALITY/PHASES OF FLIGHT	AT GATE/ A/C STAND	TAXIING IN-OUT	TAKE-OFF CLIMB	EN-ROUTE	APPROACH/ LANDING
Update of Maps	X				X
Loading of Actual Flight Plans	X				
Monitoring of Service Vehicle Movements	X	X			
Vehicle and Aircraft Fleet Management	X	X	X	X	X
ATC Clearance Delivery	X	X	X	X	X
Taxi Guidance		X			
Docking Guidance	X				
Runway Incursion Prevention		X			X
Situation Awareness/ Collision Avoidance		X	X	X	X
ADS Functionality		X	X	X	X
Accurate ETO/ETA- 4-D ATC System			X	X	X
Reduced Separation				X	
Search and Rescue		X	X	X	X
Text Messages	X	X	X	X	X
Precision Approach					X

SUBSTITUTE SHEET

CLAIMS

- 5
1. A position indicating system including a population of simultaneously participating movable stations, each station knowing its geographic position through the reception of signals from a plurality of geometrically distributed transmitters having known positions, each participating station having a transmitter for the emission in a common radio channel, of signals indicating its own geographic position, memory means being arranged for the memorization of received information from other participating stations,
- 10
- 15 characterized in that each movable station has
- a) a time base accurately controlled by time signals from said plurality of geometrically distributed transmitters, said time base defining time blocks which are normed, enumerable and form a common, accurate, predetermined, repeating
- 20 maximal frame,
- b) means for occupying a free time block in each maximal frame and for autonomously transmitting therein of a position signal in the common radio channel.
- 25
2. A position indicating system of claim 1, characterized in that said common radio channel has a frequency so determined that its range of detection is substantially limited to the line of sight, said plurality of geometrically distributed transmitters comprising satellites emitting time signals,
- 30 each participating movable station having means for calculating its geographic position and an absolute time for updating its time base using said emitted time signals.
- 35
3. A position indicating system of claim 2, characterized in that said movable stations are arranged in aircraft distributable around the earth.
4. A position indicating system of claim 3, characterized in means in each movable station for sensing a transmission

order signal from a ground station and for discontinuing said autonomous transmission on reception of said order signal and then transmitting in a ground station ordered mode, in time blocks indicated by said ground station.

5

5. A position indicating system of claim 3, characterized in that each movable station is provided with means for a systematic relocation of time block used, means comprising memory means for registering free time blocks in said maximal frame, in which no transmission from other stations is detected, said means for relocation selecting at predetermined intervals a new unoccupied time block for its transmission in the maximal frame.

15

6. A position indicating system of claim 5, characterized in that before transmission in a new selected time block, each station signals in its presently occupied time block its intention to switch to said new unoccupied block.

20

7. A position indicating system of claim 5, characterized in means in each movable station, when no unoccupied time block is detected, for appropriating a time block in use by a geographically remote movable station.

25

8. A position indicating system of claim 1, characterized in that each movable station has means for determining the geographical distance to its nearest neighbour movable station, and means for determining as a function of said distance of the number of time blocks in which to send in each maximal frame, for diminishing the load on the common radio channel.

30

9. A position indicating system of claim 1, characterized in means for using the signals from neighbouring stations instead of one or more of said plurality of geometrically distributed transmitters in satellites for determining own position when said signals from satellites are unreceived.

35

10. A position indicating system of claims 4 and 9 in combination, characterized in that said ground stations are provided with exact clocks for enabling the emission of synchronized signals in case of failure of the said satellites.

11. A positioning station for a position indicating system, which station comprises a GPS satellite signal receiver arranged to deliver the geographic position, and a transceiver for transmitting said geographic position in a radio channel, characterized in comprising a communication processor (5) connected to said satellite signal receiver (4), and to said transceiver, said radio channel being of a frequency having a physically limited range, said communication processor comprising a time base (13), a time synchronization connection between the time base and the satellite receiver, a microprocessor (10), a RAM memory (11) for collecting position signals received by the transceiver in time blocks determined by the time base, a program memory (12), a data bus (14), an address bus (15), means for accounting of position messages received from neighbouring stations and taken from said RAM memory, and means for transmitting in an autonomous mode of own position signals to said transceiver for their emission in time blocks unoccupied by other stations.

12. A positioning station of claim 11, characterized in that said range for the radio channel is substantially limited to the line of sight.

13. A positioning station of claim 10, characterized in means for sensing ground station order signals from a ground station and for transmitting after the reception of such an order signal of position signals in the radio channel merely as ordered from the ground station, instead of an autonomous sending mode.

1/4




FIG.1

SUBSTITUTE SHEET

2/4




FIG. 2

SUBSTITUTE SHEET

3/4




FIG. 3




FIG. 4




FIG. 5

4/4






FIG.6

FIG.7



INTERNATIONAL SEARCH REPORT

International Application No PCT/SE 92/00485

I. CLASSIFICATION OF SUBJECT MATTER (If several classification symbols apply, indicate all) ⁶		
According to International Patent Classification (IPC) or to both National Classification and IPC		
IPC5: G 08 G 3/02, G 08 G 5/04		
II. FIELDS SEARCHED		
Minimum Documentation Searched ⁷		
Classification System	Classification Symbols	
IPC5	G 01 S, G 08 G	
Documentation Searched other than Minimum Documentation to the Extent that such Documents are Included in Fields Searched ⁸		
SE,DK,FI,NO classes as above		
III. DOCUMENTS CONSIDERED TO BE RELEVANT⁹		
Category *	Citation of Document, ¹¹ with indication, where appropriate, of the relevant passages ¹²	Relevant to Claim No. ¹³
A	US, A, 4835537 (MANION) 30 May 1989, see column 4, line 4 - column 5, line 53; figures 1,3,4 --	1-3,11, 12
A	WO, A1, 8800379 (LMT RADIO PROFESSIONALLE) 14 January 1988, see page 2, line 17 - page 5, line 26; figure 1 --	1,2,11, 12
A	GB, A, 2155720 (STANDARD TELEPHONES AND CABLES PUBLIC LIMITED) 25 September 1985, see page 1, line 46 - line 51; page 1, line 103 - line 121; figure 1 --	4,13
A	US, A, 4380050 (J TANNER) 12 April 1983, see column 1, line 66 - column 2, line 43 -- -----	1,11
<div style="display: flex; justify-content: space-between;"> <div style="width: 45%;"> <p>* Special categories of cited documents:¹⁰</p> <p>"A" document defining the general state of the art which is not considered to be of particular relevance</p> <p>"E" earlier document but published on or after the international filing date</p> <p>"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)</p> <p>"O" document referring to an oral disclosure, use, exhibition or other means</p> <p>"P" document published prior to the international filing date but later than the priority date claimed</p> </div> <div style="width: 45%;"> <p>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention</p> <p>"X" document of particular relevance, the claimed invention cannot be considered novel or cannot be considered to involve an inventive step</p> <p>"Y" document of particular relevance, the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.</p> <p>"&" document member of the same patent family</p> </div> </div>		
IV. CERTIFICATION		
Date of the Actual Completion of the International Search	Date of Mailing of this International Search Report	
5th October 1992	07 -10- 1992	
International Searching Authority	Signature of Authorized Officer	
SWEDISH PATENT OFFICE	 GÖRAN MAGNUSSON	

**ANNEX TO THE INTERNATIONAL SEARCH REPORT
ON INTERNATIONAL PATENT APPLICATION NO.PCT/SE 92/00485**

This annex lists the patent family members relating to the patent documents cited in the above-mentioned international search report.
The members are as contained in the Swedish Patent Office EDP file on 28/08/92
The Swedish Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US-A- 4835537	89-05-30	NONE	
WO-A1- 8800379	88-01-14	EP-A-B- 0273953 FR-A-B- 2601168 JP-T- 1501177	88-07-13 88-01-08 89-04-20
GB-A- 2155720	85-09-25	AU-D- 3911685	85-09-12
US-A- 4380050	83-04-12	NONE	

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.